

VERTICAL

BUDGET Range – Solid bamboo flooring 1st price

F12VCC96

F12VOCH96

F12VOC96

Dimensions: 12 x 96 x 960 mm

Coating: Factory applied UV-varnish layer - matt appearance
Factory applied WOCA oil layer - matt appearance

Colors: Caramel, Champagne

Charger: GO2

Installation: Glued: Yes
Floating: Yes
Floorheating: yes if glued pose
Use in bathroom: Yes if glued pose and varnish coating

Wearing surface: ±4,4 mm

Box : Content: 30 planks/box (2,76 m²)
Weight: 29,5 kg

Maintenance : cfr maintenance instructions

BRINELL HARDNESS	43 N/mm ² - EN 1534 norm (Report CTIB 5229/2)
CONTRACTION COEFFICIENT	0,14% per % humidity variation
HUMIDITY DEGREE	10% at 20 °C and 65% relative humidity 8% at 20 °C and 50% relative humidity
DENSITY	740 kg/m ³
FIRE NORM	CFLS1 if glued pose
FORMALDEHYDE EMISSION	0,04 mg/ m ² h - EN 717-2 norm (Report CTIB 5229/2)
THERMIC RESISTANCE	0,072 m ² K/W - EN 12664 norm (Report CTIB 5229/2)
PCP CONTENT	Below detection limit (Report CTIB 5229/2)
VOC FREE	Below detection limit – EN 15052 norm

Do not forget the accessoires!

