

BAMBOOTouch Outdoor Massif

Massive Espresso XTR

D20BES137.185
D20BES178.185

Dimension:	20 x 137 x 1850 mm 20 x 178 x 1850 mm
Finish:	Grooved blades - head of blade tongued
Decor :	1 side smooth - 1 side grooved French comb style
Color:	Espresso (dark brown)
Installing:	on joists with clips (see installation sheet)
Pallet :	Content for 18 mm = 216 blades/pallet (54.75 m ² /pallet) Content for 1860 mm = 120 blades/pallet (36.17 m ² /pallet)
Maintenance :	see maintenance sheet for BambooTouch Outdoor Massif

BRINELL HARDNESS	9.5 kg/mm ² - norm EN 1534 (Report CTIB 5229/2)
COEFFICIENT OF CONTRACTION	0,14% per % of humidity variation
HUMIDITY LEVEL	10 to 14 % if 20 °C and 65% relative humidity 8% to 20 °C and 50% relative humidity
DENSITY	1150 kg/m ³
BIOLOGICAL DURABILITY	Class 1 (EN 335)
FIRE SYANDARD	Class A (UL 723, ANSI/NFPA N°255, UBC N°8-1)
FORMALDEHYDE EMISSION	0,4 mg/ m ² h - norm GB/T17657-2013)
THERMIC RESISTANCE	Class A (UL 723,ANSI/NFPA N°255, UBC N°255, UBC N° 8-1)
RESISTANCE TO STATIC BENDING	86.9 Mpa (GB/T17657-2013)
MODULAR ELASTICITY	13970 Mpa (GB/T17657-2013)
SWELLING RATE - MAX THICKEN.	1.9% (GB/T30364-2013)
SWELLING RATE - MAX WIDTH	0.4% (GB/T30364-2013)
SLIP RESISTANCE	USRV 58 (CEN/TS15676)
TERMITES RESISTANCE	Class 8 (AWPA-2012, AWPA E1-09)

